

Lagerware Douglasie/Lärche-gehobelt

Konstruktionsvollholz KVH, Douglasie/ Lärche, Nsi, C24, trocken <20%HF, gehobelt/ egalisiert & gefast, keilgezinkt nach DIN EN 15497

Stärke	Breite					
cm	10	12	14	16	20	24
6		6,50m 13,00m		6,50m 13,00m	6,50m 13,00m	
8				6,50m 13,00m	6,50m 13,00m	6,50m 13,00m
10	6,50m 13,00m				6,50m 13,00m	
12		6,50m 13,00m		6,50m 13,00m	6,50m 13,00m	6,50m 13,00m

Konstruktionsholz, Lärche/Douglasie, gehobelt & gefast, trocken <20% HF, ohne Keilzinkung (Kreuzholz 9x9cm, 10x10cm, 12x12cm)

Stärke	Breite								
cm	6	8	9	10	12	14	16	20	24
4	5,00m							5,00m	
6		5,00m		5,00m	4,00m 5,00m		4,00m 5,00m	5,00m	
8					5,00m		5,00m	5,00m	5,00m
9			4,00m						
10				3,00m 4,00m 5,00m				5,00m	
12					2,50m 3,00m 4,00m 5,00m		5,00m	5,00m	5,00m
14						5,00m			