

Lagerware

Konstruktionsholz Douglasie/Lärche

Konstruktionsvollholz KVH, Douglasie/ Lärche, Nsi, C24, trocken <20%HF, gehobelt/ egalisiert & gefast, keilgezinkt nach DIN EN 15497

Stärke	Breite					
cm	10	12	14	16	20	24
6		6,50m 13,00m		6,50m 13,00m	6,50m 13,00m	
8				6,50m 13,00m	6,50m 13,00m	6,50m 13,00m
10	6,50m 13,00m				6,50m 13,00m	
12		6,50m 13,00m		6,50m 13,00m	6,50m 13,00m	6,50m 13,00m
14			6,50m			
16				6,50m		

(Duolam)

Konstruktionsholz, Lärche/Douglasie, gehobelt & gefast, trocken <20% HF, ohne Keilzinkung (Kreuzholz 9x9cm, 10x10cm, 12x12cm)

Stärke	Breite									
cm	5,8	6	8	9	10	12	14	16	20	24
3,8	3,00m 4,00m 4,50m 5,00m									
4		5,00m							5,00m	
6			4,00m 5,00m		5,00m	4,00m 5,00m		4,00m 5,00m	5,00m	
8						5,00m		5,00m	5,00m	5,00m
9				4,00m						
10					3,00m 4,00m 5,00m				5,00m	
12						2,50m 3,00m 4,00m 5,00m		5,00m	5,00m	5,00m
14							5,00m			